


Coperion K-Tron Product Specification

Loss-in-Weight Twin Screw Feeder

K-ML-KT35



- Ext. communication to Host System
- A Feeder
 - B Weighing System
 - C Control Module
 - D Operator Interface

Each Coperion K-Tron Weigh feeder consists of the components A, B, C and D.

Component A is specified here.

Application

Gravimetric feeding of free flowing to very poorly flowing powders (e.g. lumpy, moist or bridge building materials) as well as fibers, flakes and other bulk materials.

Design

Twin screw feeder with interchangeable feeding tools suspended in a three-point weighing system. All parts in contact with the material being fed are stainless steel. Feeding equipment is easy to disassemble. The horizontal agitator gently moves the bulk material to the large throat and then into the screws. Feeder screws are easily interchangeable.


This equipment conforms to CE standards regarding EMC and safety.

Controller: (see separate data sheets)

The SmartConnex™ control system allows individual or multi-component control. Interface-modules for computer communications are installed in the control module.

Hazardous Location Options: (see sheet I-000002)





- NEC Class II, Div. 2, Groups F & G / Class II, Div. 1, Groups F & G
- Class I, Div. 2, Groups C & D / Class I, Div. 1, Groups C & D
- ATEX 3D/3D, 3D/2D, 3G/3G, 2GD/2GD (outside/inside)



Feed Screws and Sample Feed Rates

Feeder screws are determined based on the material being fed. The theoretical throughput range of 1:100 is influenced by feeder configuration and material characteristics. The sample feed rates below were tested with a free-flowing material (semolina, bulk density 0.783 kg/dm³).

Attention: Actual feed rates depend on individual material characteristics. At higher screw speeds a poorly flowing powder will not achieve the full throughput possible with a free-flowing material due to reduced degree screw fill. For feed rates at the upper or lower limits of the theoretical range, check with a Coperion K-Tron Test Lab.

Pitch		 Twin concave screws	 Twin auger screws	 Twin spiral screws	 Double auger screws	Screw speed range	Gearbox type
coarse pitch	dm³/h	16.3 - 1466	28.7 - 2346	20 - 1446	25.9 - 1772	6 - 621	A
	ft³/h	0.58 - 51.75	1.01 - 82.81	0.71 - 51.04	0.91 - 62.55		
	dm³/h	8 - 727	14 - 1184	8.9 - 726	11.6 - 905	3 - 297	B
	ft³/h	0.28 - 25.66	0.49 - 41.8	0.31 - 25.63	0.41 - 31.95		
fine pitch	dm³/h	3.1 - 315	5.6 - 521	3.6 - 329	4.6 - 430	1.3 - 128	C
	ft³/h	0.11 - 11.12	0.2 - 18.39	0.13 - 11.61	0.16 - 15.18		
	dm³/h	10.5 - 952	14.9 - 1418	12.2 - 1058	13.8 - 1298	6 - 621	A
	ft³/h	0.37 - 33.61	0.53 - 50.06	0.43 - 37.35	0.49 - 45.82		
fine pitch	dm³/h	5.2 - 460	7.3 - 689	5.1 - 520	6.7 - 639	3 - 297	B
	ft³/h	0.18 - 16.24	0.26 - 24.32	0.18 - 18.36	0.24 - 22.56		
	dm³/h	2.3 - 201	2.6 - 300	1.9 - 231	2.5 - 278	1.3 - 128	C
	ft³/h	0.08 - 7.1	0.09 - 10.59	0.07 - 8.15	0.09 - 9.81		

Feed rates shown are with DC motor and KCM controller (Range 1:100 / Max. motor speed 2000 RPM). For feed rates with vector-duty AC motor with speed pick-up and KCM controller multiply values by 0.875 (Range 1:100 / Max. motor speed 1750 RPM).

Coperion K-Tron Product Specification Loss-in-Weight Twin Screw Feeder

K-ML-KT35

Configuration

Description	Selection	Remarks	Weight kg (lb)
Vertical agitator	KS: 230/400 VAC 180, 250 W IP55	4D (50 L, 80 L) 6D (110 L, 180 L)	25 (55) 36 (79)
Cover	KA: 115/230 VAC 0.25, 0.33 HP or 100/200 VDC 0.33 HP	4D 6D	2 (4.4) 3 (6.6)
Weigh bridge 3 x K-SFT:	30 kg 66 lb 60 kg 132 lb 90 kg 198 lb 120 kg 264 lb	IP65, NEMA 4 Gross weigh bridge capacity = 3 x K-SFT	
Extension hopper		4D or 6D	see below
Horiz. agitator			0.7 (1.5)
Trough	5 L		2.5 (5.5)
Gearbox	A B C		15 (33)
Motor	100/200 VDC 450 W IP65	standard: 450 W DC	12 (26.4)
Screws	CKS: 3x230 VAC CKA: 3x220 VAC 370/450 W IP65	see page 1	2 (4.4)
Outlet	Horiz. outlet Vertical outlet Pressure compensation	standard: horiz. outlet	1 (2.2)

Materials:

Material contact parts*: Stainless steel
DIN 1.4404, 1.4435 (AISI 316L)
DIN 1.4409 (ASTM A743 CF3M)
*Horiz. agitator: DIN 1.4034 (AISI 420) standard
DIN 1.4404 (AISI 316L) option
Seals: PTFE, Neoprene, Silicon
Painting: Light gray RAL 7035

Weighing Range:

Gross weighbridge capacity (e.g. 3 x 60 = 180 kg) less total feeder weight and less 10% reserve

Temperature-Limits:



Ambient: 0...40°C [32...104°F]
Material: 0...50°C [32...122°F]
for other material temperatures contact factory

Dimensions mm [in]

Options

- 1 Hopper
- 2 Vertical outlet
- 3 Special paint
- 4 Extended screws

Volume dm³ [ft³]	H mm [in]	D mm [in]	Weight kg [lb]
Asymmetrical Hoppers			
50 [1.76]	615 [24.2]	400 [15.75]	7 [15.4]
80 [2.8]	869 [34.2]	400 [15.75]	11 [24.2]
110 [3.88]	922 [36.3]	600 [23.62]	17 [37.4]
180 [6.4]	1176 [46.3]	600 [23.62]	23 [50.6]
250 [8.8]	1430 [57.2]	600 [23.62]	29.5 [64.9]
320 [11.3]	1684 [66.3]	600 [23.62]	35 [77]



Caution: these measurements are for general reference only. Please consult dimensional drawing for exact measurements